

Please take a few minutes to read this operating instruction and user guide.

OPERATING INSTRUCTIONS

- 1 Before opening a new aisle please make sure that no one is in any aisle.
- 2 Disengage the central push/pull lock on the central boss on the hand wheel.
- 3 When in the required position re-engage push/pull lock by pushing in the central hand wheel boss.
- 4 Move one mobile at a time (only) by turning the hand wheel either left or right.
- 5 Operate the units with care, please do not allow units to collide with each other or rack end stops. This could damage the units and dislodge stored goods.
- 6 Make sure all tracks are clear of any obstructions (see maintenance procedure).
- 7 Please check with our technical department if you have any further queries.

DO NOT:

Climb on any of the mounted shelving systems
Move more than one mobile base at a time
Collide mobile bases together

DAILY CHECKS

- 1 Ensure that no materials are protruding from the shelves or left in the aisles as bases will not close correctly and bases could be damaged.
- 2 Keep all tracks clear of any obstructions, clean and clear i.e. paper clips & rubber bands.
- 3 Pick up any debris that falls upon the tracks.
- 4 Ensure mobile bases are moving freely and squarely to the tracks.
- 5 Make sure that all hand wheels are operating correctly and that push/pull lock is operating freely.

ANNUAL CHECKS

Although this Mobilis Mobile Shelving System is designed to need little maintenance, the following check should be carried out annually or more often if the installation is heavily used.

- 1 Check wheels and tracks for any wear or scoring.
- 2 Check mobile bases are running square and true to the tracks.
- 3 Check running surface and track and capstan drive for wear.
- 4 Check all hand wheels are fitted securely and operating freely.
- 5 Check all drive shaft fixings for wear.
- 6 Check that the shelving system is securely fixed to the mobile bases and is sitting squarely onto the bases.

CLEANING

Vacuum track weekly.
Pick up all debris from tracks, bases and floor.
Do not clean tracks with oil based cleaning substances.
Clean with damp cloth and non-alkaline soap solution.
Do not allow flooring to get wet.



manufacture